

(12) INTERNATIONAL APPLICATION PUBLISHED IN ACCORDANCE WITH THE
INTERNATIONAL PATENT COOPERATION TREATY (PCT)

(19) Worldwide Organization for Intellectual Property
International Office

(43) International Publication Date
December 23, 2004 (12/23/2004)

(10) International Publication Number
PCT
WO 2004/111373 A1

(51) International Patent Classification (IPC Class)⁷: E05F 15/12

(21) International Reference Number: PCT/DE2004/000322

(22) International Application Date:
February 20, 2004 (20/20/2004)

(25) Language submitted in: German

(26) Publication Language: German

(30) Priority Data:
103 25 232.0 June 4, 2003 (06/04/2003) DE

(71) Applicant (for all designated countries with the exception of the
U.S.): ADAM OPEL AG [DE/DE]; Patent Division / L1-02, 65423
Rüsselsheim (DE).

(72) Inventor; and

(75) Inventor/Applicant (for U.S. only): SCHENKENBERGER, Jens
[DE/DE]; Rangenbergstrasse 24, 60388 Frankfurt (DE).

BOMMELMANN, Cord [DE/DE]; An den Riehen 8, 32369
Rahden (DE). HALLIK, Matthias [DE/DE]; Blütenstrasse
12, 65207 Wiesbaden (DE). VERHEE, Patrick [FR/SE];
Stora Nygatan 11, S-411 08 Göteborg (SE).

(81) Designated Countries (for any available national type of
protection unless otherwise specified): AE, AG, AL,
AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH,
CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES,
FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated Countries (for any available national type
of protection unless otherwise specified): ARIPO (BW,
GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM,

[continued on the following page]

(54) Title: HINGE DEVICE

(57) Abstract: Disclosed is a hinge device (2, 22) comprising a lever (6) that is provided with two top parts (4, 5). Said two top parts (4, 5) are used for assembling the lever (6) and are pivotable about one respective pin located at the ends of the lever (6). Two traction ropes (8, 9) are provided which grip the two top parts (4, 5) at gripping points (12, 13, 16, 17) located on different sides of a plane that is defined by the two pins.

WO 2004/111373 A1

ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For explanations of the two-letter codes and other abbreviations please refer to the explanations ("Guidance Notes on Codes and Abbreviations") at the beginning of each regular issue of the PCT Gazette.

Published

- *with international search report.*